



15 Rewe Street, Brooklyn, NY 11211 • (800) DOORS 4 U • (718) 963-1111 • Fax (718) 387-7941

STANDARD PARTICLE CORE DOOR

All Manhattan Door Corporation doors are manufactured to meet or exceed NWWDA Industry Standards and AWI Quality Standards.

- MAXIMUM SIZE:** 4-0 wide, 10-0 high.
- THICKNESS:** 1 $\frac{3}{8}$ ", 1 $\frac{3}{4}$ ", 2" and 2 $\frac{1}{4}$ ".
- CORE:** Particle core – average density 28 to 32 pounds per cubic foot.
- ADHESIVE:** Type II (water-resistant).
- FACE:** Standard 3-ply wood veneer of all grades, approximately $\frac{1}{8}$ " thick. Stock wood veneers: Anigre, Cherry, Birch, Lauan, Mahogany, Maple, Red Oak, White Oak, and Walnut. Stock engineered facings: Hardboard, Primed Hardboard, and various molded-panel styles.
- STILES:** 1 $\frac{1}{4}$ " softwood stiles are standard. Hardwood stiles are special request. All dimensions prior to factory trimming and prefitting.
- RAILS:** 2 $\frac{1}{2}$ " softwood or MDF rails are standard/mill option. Hardwood rails are special request. All dimensions prior to factory trimming and prefitting.
- MACHINING:** Complete machining to your specifications by special request.

