



15 Rewe Street, Brooklyn, NY 11211 • (800) DOORS 4 U • (718) 963-1111 • Fax (718) 387-7941

STANDARD HOLLOW CORE DOOR

All Manhattan Door Corporation doors are manufactured to meet or exceed NWWDA Industry Standards and AWI Quality Standards.

- MAXIMUM SIZE:** 4-0 wide, 10-0 high.
- THICKNESS:** 1 $\frac{3}{8}$ " and 1 $\frac{1}{4}$ ".
- CORE:** Expanded corrugated core meeting NWWDA Industry Standards.
- ADHESIVE:** Type II (water-resistant).
- FACE:** Standard 3-ply wood veneer of all grades, approximately $\frac{1}{8}$ " thick. Stock wood veneers: Anigre, Cherry, Birch, Lauan, Mahogany, Maple, Red Oak, White Oak, and Walnut. Stock engineered facings: Hardboard, Primed Hardboard, and various molded-panel styles.
- STILES:** 1 $\frac{1}{4}$ " softwood stiles are standard. Hardwood or MDF stiles are special request. All dimensions prior to factory trimming and prefitting.
- RAILS:** 1 $\frac{7}{8}$ " wood or MDF rails are standard/mill option. 2 $\frac{1}{2}$ " or 5" wood rails are special request. All dimensions prior to factory trimming and prefitting.
- LOCKBLOCK:** One (1) piece 2 $\frac{5}{8}$ " X 16" particle board; two (2) pieces are special request. 2 $\frac{5}{8}$ " X 20" wood is special request.
- MACHINING:** Complete machining to your specifications by special request.

