



15 Rewe Street, Brooklyn, NY 11211 • (800) DOORS 4 U • (718) 963-1111 • Fax (718) 387-7941

STANDARD MINERAL CORE DOOR: 45-MINUTE FIRE-RATED

*All Manhattan Door Corporation doors are manufactured to meet or exceed
NWWDA Industry Standards and AWI Quality Standards.*

LABEL SERVICE: Warnock Hersey listing provided by Intertek Testing Services NA, Inc.

MAXIMUM SIZE: 4-0 wide, 10-0 high (single door);
8-0 wide, 9-0 high (pair of doors).

THICKNESS: 1¾" only.

CORE: Incombustible, non-asbestos mineral core, engineered to meet label requirements.

ADHESIVE: Type II (water-resistant).

FACE: Standard 3-ply wood veneer of all grades, approximately ⅛" thick. Stock wood veneers: Anigre, Cherry, Birch, Lauan, Mahogany, Maple, Red Oak, White Oak, and Walnut. Stock engineered facings: Hardboard and Primed Hardboard.

STILES: GP Firestop II Edge Composition comprised of ¾" width of composition and 9/16" width of Douglas Fir on composition. All dimensions prior to factory trimming and prefitting.

RAILS: 2" GP Firestop Rail Composition for both top and bottom rails. All dimensions prior to factory trimming and prefitting.

STANDARD SIZE OPENINGS: 1296 sq. in., maximum width 30", maximum height 54"; metal vision panel ¼" wire glass. Other glazing options change size standards.

MACHINING: Complete machining to your specifications by special request.

