



15 Rewe Street, Brooklyn, NY 11211 • (800) DOORS 4 U • (718) 963-1111 • Fax (718) 387-7941

STANDARD MINERAL CORE DOOR: 90-MINUTE FIRE-RATED

*All Manhattan Door Corporation doors are manufactured to meet or exceed
NWWDA Industry Standards and AWI Quality Standards.*

LABEL SERVICE: Warnock Hersey listing provided
by Intertek Testing Services NA, Inc.

MAXIMUM SIZE: 4-0 wide, 10-0 high (single door);
8-0 wide, 9-0 high (pair of doors).

THICKNESS: 1¾" only.

CORE: Incombustible, non-asbestos
mineral core, engineered to
meet label requirements.

ADHESIVE: Type II (water-resistant).

FACE: Standard 3-ply wood veneer of
all grades, approximately ⅛" thick.
Stock wood veneers: Anigre,
Cherry, Birch, Lauan, Mahogany,
Maple, Red Oak, White Oak,
and Walnut. Stock engineered
facings: Hardboard and Primed
Hardboard.

STILES: GP Firestop II Edge Composition
comprised of 1" width of
composition and 9/16" width of
Douglas Fir on composition. All
dimensions prior to factory
trimming and prefitting.

RAILS: 2" GP Firestop Rail Composition
for both top and bottom rails. All
dimensions prior to factory
trimming and prefitting.

**STANDARD
SIZE OPENINGS:** 100 sq. in., maximum width 10",
maximum height 33"; metal vision
panel ¼" wire glass. Other glazing
options change size standards.

MACHINING: Complete machining to your
specifications by special request.

