



15 Rewe Street, Brooklyn, NY 11211 • (800) DOORS 4 U • (718) 963-1111 • Fax (718) 387-7941

## STANDARD 20-MINUTE FIRE-RATED DOOR

*All Manhattan Door Corporation doors are manufactured to meet or exceed NWWDA Industry Standards and AWI Quality Standards.*

**LABEL SERVICE:** Warnock Hersey listing provided by Intertek Testing Services NA, Inc.

**MAXIMUM SIZE:** 4-0 wide, 10-0 high (single door).

**THICKNESS:** 1 $\frac{3}{4}$ " only.

**CORE:** Particle core – average density 28 to 32 pounds per cubic foot; or Laminated Strand Lumber.

**ADHESIVE:** Type II (water-resistant).

**FACE:** Standard 3-ply wood veneer of all grades, approximately  $\frac{1}{8}$ " thick. Stock wood veneers: Anigre, Cherry, Birch, Lauan, Mahogany, Maple, Red Oak, White Oak, and Walnut. Stock engineered facings: Hardboard, Primed Hardboard, and various molded-panel styles.

**STILES:** 1 $\frac{1}{4}$ " softwood stiles are standard. Hardwood stiles are special request. All dimensions prior to factory trimming and prefitting.

**RAILS:** 2 $\frac{1}{2}$ " softwood rails are standard. Hardwood rails are special request. All dimensions prior to factory trimming and prefitting.

**MACHINING:** Complete machining to your specifications by special request.

