




109 Kero Road, Carlstadt, NJ 07072
 Tel: 718-963-1111 Fax: 718-387-7941
 www.ManhattanDoor.com

PRODUCT DATA SHEET

FPC5-20 MIN: Standard Particleboard Core Door (5-Ply)

SPECIFICATIONS

Wood Rail



- Maximum Size:** 48" wide x 96" high. Pairs and doors above 96" high require 45minute construction. Call office for information
- Transoms:** Call office for details.
- Thickness:** 1.375", 1.75", 2.0" and 2.25"
- Core:** Particleboard LD-1 or LD-2, which complies with ANSIA208.1.
- Veneers:** Many species of natural wood veneer are available. WDMA 'A' grade, book & running match are standard. Primed Hardboard, Primed MDF, MDO and Decorative Plastic Laminate are also available.
- Stiles:** 1.25" softwood stiles are standard. Matching hardwood stiles with LSL backer (used for rigidity) are also available. All dimensions prior to factory trimming and prefitting.
- Rails:** Solid 1.25 wood rail or extra blocking upon request. All Dimensions prior to factory trimming and prefitting
- Finish:** TR-6 UV clear, custom stain to match color, or primed where applicable.
- Adhesives:** PVA meets or exceeds WDMA I.S.1-A for Type 1 flush wood door adhesive.
- Lites:** Wood lip or flush molding wood visions and metal visions frames with 1/4" glass (all types).
- Blocking:** Top rail, bottom rail, stiles, and special blocking for special hardware is available.
- Machining:** Bevel, hinge and lock, mortise lock, cardlock, pivot and other hardware preps using state of the art CNC equipment.
- Fire Rating:** 20-Minute Intertek Testing Services / Warnock Hersey Listing
Neutral Pressure
- Standards:** Meets ANSI, WDMAI.S. 1-A and AWI

Environmental / LEED Credit Contributions (Optional)

- MR 4: Recycled Content
- MR 5: Regional Materials
- MR 6: Rapidly Renewable Materials (Bamboo Veneer Only)
- MR 7: Certified Wood (FSC Pure, FSC % and FSC CW)
- IEQ 4.4: Low Emitting Materials / No Added Urea Formaldehyde



Intertek