



109 Kero Road, Carlstadt, NJ 07072
 Tel: 718-963-1111 Fax: 718-387-7941
 www.ManhattanDoor.com

Available Core Options



PRODUCT DATA SHEET LAM-HPDL

High Pressure Laminate Door

SPECIFICATIONS

| | |
|---------------|---|
| Maximum Size: | 48" wide x 120" high, Pairs: 96" x 120" Larger doors (up to 60" x 144") for special use are also available. Call office for information. |
| Thickness: | 1.375", 1.75", 2.0" and 2.25" |
| Core: | PC, SCL, 45, 90, 20 |
| Veneers: | All major brands Pionite Formica, Nevamar, and Wilsonart |
| Stiles: | Matching Laminate Edgeband |
| Adhesives: | PVA meets or exceeds WDMA I.S. I-A for Type I flush wood door adhesive. |
| Lites: | Vision cut out & metal vision |
| Blocking: | Special blocking for hardware available upon request |
| Machining: | Bevel, hinge and lock, mortise lock, card lock, pivot and other hardware preps using state of the art CNC equipment. |
| Standards: | Meets WDMA I.S. I-A and AWI |

Environmental / LEED Credit Contributions (Optional)

MR 4: Recycled Content
 MR 5: Regional Materials
 MR 6: Rapidly Renewable Materials (Bamboo Veneer Only)
 MR 7: Certified Wood (FSC Pure, FSC % and FSC CW)
 IEQ 4.4: Low Emitting Materials / No Added Urea Formaldehyde