



WE DO IT RIGHT, THE FIRST TIME, ON TIME, EVERY TIME.

109 Kero Road, Carlstadt, NJ 07072

T: (718) 963-1111 F: (718) 387-7941

www.ManhattanDoor.com

PRODUCT DATA SHEET

LL-SCL:

Lead-Lined

Structural Composite Lumber Core

SPECIFICATIONS

Maximum Size: 48" wide x 120" high, Pairs: 96" x 120";
Larger doors (up to 60" x 144") for special use are also available. Call office for information.

Thickness: 1.75"; 2" & 2.25" available by special request.

Core: Structural Composite Lumber Core (SCL), also known as Laminated Strand Lumber (LSL)

Lead: One sheet of 1/16" lead shielding bonded between two layers of crossbands.

Veneers: Many species of natural wood veneer are available. WDMA 'A' grade, book & running match are standard. Primed Hardboard, Primed MDF, MDO and Decorative Plastic Laminate are also available.

Stiles: 1.25" softwood stiles are standard. Matching hardwood stiles with LSL backer (used for rigidity) are also available. All dimensions prior to factory trimming and prefitting.

Rails: N/A (the SCL/LSL core is throughout the door)


Finish: TR-6 UV clear, custom stain to match color, or primed where applicable.

Adhesive: PVA meets or exceeds WDMA I.S. I-A for Type I flush wood door adhesive.

Lites: Cut-out only

Blocking: N/A

Machining: Bevel, hinge and lock, mortise lock, card lock, pivot and other hardware preps using state of the art CNC equipment.



109 Kero Road, Carlstadt, NJ 07072

T: (718) 963-1111 F: (718) 387-7941

www.ManhattanDoor.com